

Lever Action Hand Drum Pumps

Excellent for Transferring All Kinds of Liquids, up to 10 Gpm!



Model No. DM-55LHP/PP Polypropylene Lever Hand Pump

- Flow Rate: 9 Gpm, includes 2" Npt bung adapter. Wt. 8 lbs.
- Ideal for most organic acids, plating solutions, alcohols, detergents and other inorganic chemicals
- Designed to fit, 15, 30, 55 gallon drums.

Optional Maintenance Kit on Request



Model No. DM-55CLHP/PP Polypropylene Center Lever Hand Pump

- Flow Rate: 6 Gpm, includes 2" Npt bung adapter. Wt. 4 lbs.
- Ideal for most organic acids, plating solutions, alcohols, detergents and other inorganic chemicals
- Designed to fit, 15, 30, 55 gallon drums.

Optional Maintenance Kit on Request



Model No. DM-55LHP/SST Stainless Steel & Teflon Lever Hand Pump

- Flow Rate: 12 oz. per Stroke, includes 2" Npt bung adapter, Wt. 8 lbs.
- For dispensing many aggressive chemicals such as esters, ketones, alcohols and hydrocarbons.
- MOC's: SS discharge tube with a 2-piece SS suction tube & SS body.
- Designed to fit, 15, 30, 55 gallon drums.

Optional Maintenance Kit on Request



Model No. DM-55LHP/TFE Teflon & Stainless Steel Lever Hand Pump *FOR EXTREME DUTY APPLICATIONS*

- Flow Rate: 9 Gpm, with 2" Npt bung adapter, Wt. 5 lbs.
- This Teflon level hand pump is designed for tight quarters dispensing of virtually any liquid.
- Materials of Construction, (wetted parts) Teflon and 316 stainless steel.
- Designed to fit, 15, 30, 55 gallon drums.

Optional Maintenance Kit on Request



Model No. DM-55LHP/RST Ryton Lever Hand Pump

- Flow Rate: 10 Gpm, with 2" Npt bung adapter, Wt. 4 lbs.
- For dispensing a wide variety of fluids, chemicals and anything compatible with Ryton, Teflon & SS
- Designed to fit, 15, 30, 55 gallon drums.

Optional Maintenance Kit on Request



Model No. DM-55LHP/AL Aluminum Lever Hand Pump

- 12 Oz. per stroke, Materials: AL, Viton, HDPE, Wt. 16 lbs.
- Designed for transferring non-corrosive & oil based liquids compatible with pump materials
- Self priming with Lightweight aluminum body
- Drip tray catches drips from discharge spout and returns them to drum automatically
- Designed to fit, 15, 30, 55 gallon drums, with bung adapter



Model No. DM-55LHP/S? Steel Lever Hand Pump

- Flow Rate: 12 oz. per Stroke, Wt. 7 lbs.
- For dispensing a wide variety of oil based liquids and anything compatible with steel
- Designed with 2" Npt bung adapter, to fit 15, 30, 55 gallon drums.

Optional Maintenance Kit on Request



Model No. DM-55LHP/SHV Steel High Viscosity Lever Hand Pump

- Flow Rate: 18 oz. / stroke, MOC's: HDPE, AL, Neoprene, Wt. 8 lbs.
- For screened dispensing of thicker oil based liquids such as paraffin, motor oil, cutting oils, etc.
- With telescoping tube and 2" Npt bung adapter designed to fit, 15, 30, 55 gallon drums.

Optional Maintenance Kit on Request