

Rotary Drum & Tank Hand Pumps

Excellent for Transferring All Kinds of Liquids, from 6-27 Gpm!



Model No. DM-55RHP/PP Polypropylene Rotary Hand Pump

- Flow Rate: 8 Gpm, includes 2" Npt bung adapter. Wt. 3 lbs.
- Ideal for most organic acids, waxes, plating solutions, alcohols, detergents and other inorganic chemicals
- Designed to fit, 15, 30, 55 gallon drums.

Optional Maintenance Kit:

P# DM-55RHP/PP-MK, 2, Vanes, 1, spring & 1 pin, 1, gasket



Model No. DM-55RHP/SR Stainless Steel Rotary Hand Pump

- Flow Rate: 6 Gpm, includes 2" Npt bung adapter, Wt. 8 lbs.
- For dispensing aggressive chemicals such as esters, ketones, alcohols and hydrocarbons.
- MOC's: SS discharge tube with a 3-piece SS suction tube & Ryton body.
- Designed to fit, 15, 30, 55 gallon drums.

Optional Maintenance Kit:

P# DM-55RHP/PPS-MK, 2, Vanes, 1, spring & 1 pin, 1, gasket



Model No. DM-55RHP/CI Cast Iron Rotary Hand Pump

- Flow Rate: 10 Gpm, with 2" Npt bung adapter, Wt. 13 lbs.
- For dispensing petroleum products, light oils, anti-freeze, lubricating oils, transmission fluid, and other oil based fluids or solvents. Not for use with water.
- Designed to fit, 15, 30, 55 gallon drums.

Optional Maintenance Kit:

DM-55RHP/CI-MK, 2, Vanes, 1, spring & 1 pin, 1, gasket



Model No. DM-55RHP/HF HI-Flow Rotary Hand Pump

- 27 Gpm, bung adapter, MOC's: AL, steel, HDPE, IPS, cast iron, Wt. 6 lbs.
- Designed for transferring non-corrosive & oil based liquids compatible with pump MOC's
- Can empty a 55-gallon drum in less than 2 minutes
- Lightweight aluminum body
- Highly machined steel rotors and gear box
- Self priming with easy-turning hand crank
- HDPE discharge tube & 2" IPS bung adapter
- 1" NPT inlet strainer, #60 mesh, 1" NPT discharge port, 1.25" NPT inlet steel pipe suction tube



Model No. DM-55RHP/TFE Teflon Rotary Hand Pump **FOR EXTREME DUTY APPLICATIONS**

- Flow Rate: 6 Gpm, with 2" Npt bung adapter, Wt. 7 lbs.
- This Teflon rotary pump is designed to dispense virtually any liquid.
- Materials of Construction, Teflon (wetted parts) and 316 stainless steel.
- Designed to fit, 15, 30, 55 gallon drums.

Optional Maintenance Kit:

DM-55RHP/TFE-MK, 2, Vanes, 1 each, spring, pin, gasket



For best batch mixing Quality Control before pumping, ask for DRUM-MATES® TQMixing™ Guidelines.
NOTE: For easy "Pick 'n' Match", all mixer shafts, mixer drives and accessories are sold separately.
DRUM-MATES® Inc., Mixer & Pump Div., Tel: 1-800-621-3786 and 609-261-1033, Fax: 609-261-1034