


Convoluting Dispensing Hose

For transferring a wide range of chemicals and other liquids



Product Code: DM-85CDH

This fine quality, economical, highly flexible, thin-wall, convoluted (ribbed) polypropylene transfer hose has a very high chemical resistance. The black hose includes UV inhibitors with excellent UV resistance for both outdoor or indoor applications. It is intended for low pressure dispensing of a wide range of liquids at up to 25 Psi.



Hose mounts easily with clamp

General Applications:

- 1) Pump or gravity feed transfer hose
- 2) Process equipment dispensing
- 3) Machine day-tank or storage reservoir transfer
- 4) Equipment or appliance fluid transfer hose
- 5) Sump waste removal and many other applications

Liquid Types:

For general liquids compatible with polypropylene including chemicals, acids, alkalis, water, bio-chemicals, photo chemicals, liquid fertilizers, pesticides, agricultural chemicals, inks and dyes, paints and other surface coatings, polymers, adhesives, machining oils, coolants, solvents, cleaners, brine, enzymes, waste liquids and many others...

Material Grades:

Virgin A-grade, black copolymer polypropylene (CPP) with UV inhibitors

Material Style:

Convoluting (a ribbed corrugation shape)

Bending Features:

Approximate 2" radius, dependent on hose size, temperature & other variables.

Available Sizes:

1/2", 3/4", 1.0", 1.5", 2.0" internal diameter

Cuffing Frequency:

Every foot, or in segment lengths requested with 1 foot increments.

Cuff Length:

1 1/4" length for 3/4" hose, other cuff sizes may vary

Temperature Range:

Operating temperature range, 25° to 125°F

Pressure Capacity:

Nominal Rating, Maximum 25 psi, Burst Pressure: approximately 125 Psi

Hose Length:

15.0 foot coil lengths; other lengths up to 50 ft. available on request

Hose Connections:

Hose is inter-connectable with accessory "tube connectors" for additional lengths

Package Weight:

Varies with hose size: E.g. for 3/4" ID, 28 lbs. per 375.0 ft. (25x 15 ft. coils)

Hose Options:

Now in 3/4" ID. Product runs in other sizes or in translucent polypropylene require a 50% non-refundable deposit with order on a minimum 5,000 foot run.



DRUM-MATES® equipment assemblies are provided as separate components each sold on a separate basis. Ask for literature on DRUM-MATES® drum & IBC mixers, drum tumblers, drum & IBC pumps & hand nozzles. DRUM-MATES® Inc., Drum Mixer & Pump Div., Tel: 1-800-621-3786 and 609-261-1033, Fax: 609-261-1034